



[TELCO USA INC.](#)

## SMR6106AP5

Series 6000 Receiver

Item #105795059

### PRODUCT DETAILS

- 6100 Series
- 10 - 30 Volt DC Supply Voltage
- NPN Output
- NO Contacts
- 5 m Cable Connection

---

## SPECIFICATIONS

OPERATION TEMPERATURE [MIN]	-20 °C
HYSTERESIS	Approx. 30%
OUTPUT	NPN
SEALING CLASS	IP 67
SHORT CIRCUIT PROTECTION	Yes
OPERATION TEMPERATURE [MAX]	60 °C
TYPE	Receiver
CONNECTION	5 m Cable
HOUSING SIZE	10 mm Round
CURRENT CONSUMPTION	10 mA @ 32 V dc
RANGE [MAX]	6 m
MAXIMUM OUTPUT CURRENT	100 mA
SERIES	6100
CONTACTS	Normally Open
SUPPLY VOLTAGE	10 to 30 Volt DC
OPERATION FREQUENCY [MAX]	100 Hz
OUTPUT INDICATOR	Yellow LED

RESPONSE TIME	5 ms/5 ms
HOUSING MATERIAL	Polycarbonate
LIGHT IMMUNITY @ 20%	> 50,000 lux
WEIGHT	0.5 LB

© 2023 APPLIED INDUSTRIAL TECHNOLOGIES. ALL RIGHTS RESERVED.

1 APPLIED PLAZA  
CLEVELAND, OH 44115  
UNITED STATES